

ENERGIE CONVENTIONELLE
POUR TRANSFERT DE FLUIDE

XL Techniques

XL 300



Conformity
ATEX

The XL 300 series for industrial applications is the result of the expertise of XL Techniques in the forecourt domain.

XL 300 is the guarantee of the service of XL Techniques and the reliability of a sustainable investment.

XL 300 is ideal for the industrial filling station.

Fuel types: Petrol | Diesel | RNG

Flow rate: 40, 80, 120 liters per minute

Dimensions : 430 x 450 x 1536 mm

Weight : 50 to 120 Kg

Certificate: INERIS-EQEN N°027378/13

Construction: Epoxy coated galvanised steel

Meter: Positive Movement

Metering precision: $\pm 0,3\%$

Pump: Pumping unit, with strainer filter and a check valve

Motor: 3 phases, 50/60HZ EEX

Filter: Stainless steel, reusable, 100 μ , easy clean

Nozzle: Automatic Nozzle ZVA ELAFLEX



Options:

Suction version - Power supply 1-phase - Hose mast
Nonstandard colors and livery - Satellite connection
- Safety breakaway coupling - Emergency stop
button - Different hose length - Integration of fleet
management systems (all types) - Additional filtering

XL Techniques

5 RUE DES GRANDES PIÈCES - ZI EURESPACE SUD
25 770 SERRE-LES-SAPINS
03 81 41 31 27 - WWW.XLTECHNIQUES.COM